

SPECIFICATIONS

| | |
|--------------------------|---|
| Construction | Multi Level loop |
| Yarn | 100% Nylon |
| Colour system | 100% Solution Dyed |
| Stitches & Gauge | 1/12 (40 Stitches/10 Cm) |
| Total Tufted Pile Weight | 750 GSM (22 Oz/Yd ²) |
| Total Weight | 4200 gm/m ² (+/- 100gm) |
| Pile Height | 2.0~6.0mm (+/-0.5mm) |
| Primary Backing | Non Woven |
| Secondary Backing | High Performance Precoat PVC reinforced with Fiberglass |
| Tile Size | 25cm X 100cm |
| Packing | 20 Tiles/Box (5.00 SQM) |
| Area of Use | Heavy Commercial |
| Fire Class | Cfl-s1 |
| Formaldehyde | CRI Identification 20201027-III133 17X |
| Hexapod Test | Change in appearance = 3,5 Change in color = 3-4 (BS EN ISO 9405:2017) |
| Critical Radiant Flux | 5.0 kW/m ² |
| Certifications | TUV ISO 9001:2015, KAN, CRI+, Singapore Green Building Council K3L No = 21-D-000204 TKDN No = 1474/SJ-IND.8/TKDN/5/2021 |