

Construction	Multi Level loop (Endless Design)	
Yarn	100% Nylon AE	
Colour system	100% Solution Dyed	
Stitches & Gauge	1/10 (36/10 Cm) 	
Total Tufted Pile Weight	850 GSM (25 Oz/Yd2)	
Total Weight	5200 gm/m ² (+/- 5%)	
Pile & Total Height	2.0~5.0mm (+/-0.5mm) & 8.00mm (+/-1.0mm)	
Primary Backing	Non Woven (Lutrador by Freudenberg)	
Secondary Backing	High Performance Precoat PVC reinforced with Fiberglass	
Tile Size	50cm X 50cm	
Packing	20 Tiles/Box (5.00 SQM)	
Area of Use	Class 33	Heavy Commercial
Fire Class	EN13501-1:2018	Cfl-s1
Formaldehyde	CRI Identification 20201027-II133 17X	
Hexapod Test	BS EN ISO 9405:2017	Change in appearance = 3,5 Change in color = 3-4
Critical Radiant Flux	ASTM D-7330	3.8 kW/m2
Certifications	TUV ISO 9001:2015, TUV ISO 14001:2015, KAN, CRI+, Singapore Green Building Council, K3L No = 21-D-000204 TKDN No = 1628/SJ-IND, 8/E-TKDN/2/2025	